TEMPOMATIC MIX 2 electronic mixer

Ref. 49400615

Battery-operated, Ø 15mm conical inlets

2024 UK public price excluding VAT: £686.50



DESCRIPTION

TEMPOMATIC MIX 2 electronic mixer - Ref. 49400615

Deck-mounted electronic basin mixer:

Independent IP65 electronic control unit.

Battery-operated with 123 6V Lithium batteries.

Flow rate pre-set at 4 lpm at 3 bar, adjustable from 1.4 - 6 lpm.

Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use). Shock-resistant infrared presence detection sensor.

Chrome-plated solid brass body.

PEX flexibles with filters and reduced-stagnation solenoid valves \emptyset 15mm for compression fittings.

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Side temperature control with adjustable maximum temperature limiter.

Solenoid valves are upstream of the mixing chamber.

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Total hygiene: no manual contact



85% water savings



Independent IP65 electronic control unit




Anti-bacterial proliferation duty flush

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 2 electronic mixer - Ref. 49400615

Supply	6V battery
Connector	M1/2" Ø 15mm
Technology	Electronic
Drop height	125mm
Spout length	145mm
Flow rate	4 lpm
Norms	CE
Warranty	30 g



© DELABIE