

SECURITHERM shower panel

Ref. 79240015

Electronic battery-operated thermostatic

2026 UK public price excluding VAT: £1,157.33



DESCRIPTION

SECURITHERM shower panel - Ref. 79240015

Thermostatic electronic shower panel:

Anodised aluminium shower panel for wall-mounted, exposed installation.

With top inlet via in-line stopcocks and Ø 15mm conical inlets.

SECURITHERM thermostatic shower mixer.

Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.

Anti-scalding failsafe: automatic shut-off if cold water fails.

Anti-cold showers function: automatic shut-off if hot water fails.

Thermal shocks are possible.

Battery-operated with CR-P2 223 6V Lithium battery.

Infrared presence detection. Shower starts when hand is 4cm from the sensor.

Shuts off on demand or automatically after ~60 seconds.

Duty flush (~60 seconds every 24 hours after the last use).

Flow rate set at 6 lpm at 3 bar.

Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.

Concealed fixings.

Filters and non-return valves.

Electronic shower panel suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 79240015

Supply	6V battery
Connector	M1/2" Ø 15mm
Technology	Electronic
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Warranty	30 YEAR WARRANTY

ADVANTAGES



Total hygiene: operate without manual contact



Duty flush limits bacterial proliferation



Thermostatic temperature regulation



Instant shut-off if cold water supply fails

