DELABIE

SECURITHERM shower panel

Ref. 79240015

Electronic battery-operated thermostatic

2024 UK public price excluding VAT: £1,090.89

DESCRIPTION

SECURITHERM shower panel - Ref. 79240015

Thermostatic electronic shower panel: Anodised aluminium shower panel for wall-mounted, exposed installation. With top inlet via in-line stopcocks and Ø 15mm conical inlets. SECURITHERM thermostatic shower mixer. Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C. Anti-scalding failsafe: automatic shut-off if cold water fails. Anti-cold showers function: automatic shut-off if hot water fails. Thermal shocks are possible. Battery-operated with CR-P2 223 6V Lithium battery. Infrared presence detection. Shower starts when hand is 4cm from the sensor. Shuts off on demand or automatically after ~60 seconds. Duty flush (~60 seconds every 24 hours after the last use). Flow rate set at 6 lpm at 3 bar. Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation. Concealed fixings. Filters and non-return valves. Electronic shower panel suitable for people with reduced mobility. 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 79240015	
Supply	6V battery
Connector	M1/2'' Ø 15mm
Technology	Electronic
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Warranty	



ADVANTAGES



Total hygiene: operate without manual contact

Ш.

Thermos

proliferation

Thermostatic temperature regulation

Duty flush limits bacterial



Instant shut-off if cold water supply fails

