

SECURITHERM shower panel

Ref. 79230015

Thermostatic time flow

2025 UK public price excluding VAT: £916.80

DESCRIPTION

SECURITHERM shower panel - Ref. 79230015

Time flow thermostatic shower panel:
Anodised aluminium shower panel for wall-mounted, exposed installation.
Top inlet via in-line stopcocks and conical Ø 15mm inlets.
SECURITHERM thermostatic shower mixer.
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C
Anti-scalding safety: automatic shut-off if cold or hot water supply fails.
Anti-cold showers function: automatic shut-off if hot water fails.
Thermal shocks are possible.
Soft-touch operation.
Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.
Time flow shower valve ~30 seconds.
Flow rate 6 lpm at 3 bar.
Concealed fixings.
Filters and non-return valves.
Time flow shower panel suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 79230015

Connector	M½" Ø 15mm
Technology	Time flow
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	ACS
Warranty	30 YEAR WARRANTY



ADVANTAGES



Thermostatic control



Instant shut-off if cold water supply fails



80% water savings



Aluminium body, brass controls

