

Sequential thermostatic shower mixer

Ref. H964015

SECURITHERM sequential mixer, top outlet

2026 UK public price excluding VAT: £434.31



DESCRIPTION

Sequential thermostatic shower mixer - Ref. H964015

SECURITHERM thermostatic sequential shower mixer.
Thermostatic sequential mixer: opens and closes with cold water.
Mixer with no non-return valves (limits bacterial proliferation).
No risk of cross flow between hot and cold water.
Sequential mixer with anti-scalding safety: shuts off automatically if cold water supply fails.
Prevents cold showers: shuts off automatically if hot water supply fails.
Securitouch thermal insulation prevents burns.
Scale-resistant thermostatic sequential cartridge controls flow rate and temperature.
Temperature can be adjusted from cold water to 39°C with maximum temperature limiter set at 39°C.
Thermal shocks are possible.
Body with smooth interior and low water volume (reduces niches where bacteria can develop).
Flow rate regulated at 9 lpm.
Chrome-plated brass body and Hygiene control lever L. 100mm.
M3/4" top shower outlet.
Wall-mounted mixer with inline STOP/CHECK connectors, M1/2" M3/4".
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Sequential mixer suitable for people with reduced mobility.
Shower mixer with 30-year warranty.

ADVANTAGES



SECURITHERM: Anti-scalding safety



Securitouch thermal insulation prevents burns



No non-return valves on the inlets



Sequential open and closing on cold water

TECHNICAL CHARACTERISTICS

Sequential thermostatic shower mixer - Ref. H964015

Connector	3/4"
Technology	SECURITHERM Securitouch sequential thermostatic mixer
Width	184mm
Flow rate	9 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	
Warranty	

