

Sequential thermostatic shower mixer

Ref. H963015

SECURITHERM mixer with no non-return valve, bottom outlet

2024 UK public price excluding VAT: £381.64







DESCRIPTION

Sequential thermostatic shower mixer - Ref. H963015



SECURITHERM thermostatic sequential shower mixer.
Thermostatic sequential mixer: opens and closes with cold water.
Mixer with no non-return valves on the inlets (reduces bacterial proliferation).
No risk of cross flow between hot and cold water.
Sequential mixer with anti-scalding failsafe: shuts off immediately if cold water supply fails.
Prevents cold showers: shuts off immediately if hot water supply fails
Securitouch thermal insulation prevents burns.
Scale-resistant thermostatic sequential cartridge adjusts the flow rate and the temperature.
Temperature can be adjusted from cold water to 39°C with maximum temperature limiter set at 39°C.
Thermal shocks are possible.
Body with smooth interior and low water volume (reduces niches where bacteria can develop).
Flow rate regulated at 9 lpm.
Chrome-plated brass body and Hygiene control lever L. 100mm.
M1/2" bottom shower outlet.
Wall-mounted mixer with M1/2" M3/4" inline STOP/CHECK.
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Sequential mixer suitable for people with reduced mobility.
Shower mixer with 30-year warranty.

ADVANTAGES

-  Sequential, opens/closes with cold water
-  No non-return valves on the inlets
-  SECURITHERM: optimal anti-scalding safety
-  Thermostatic: complete temperature stability

TECHNICAL CHARACTERISTICS

Sequential thermostatic shower mixer - Ref. H963015

Connector	M1/2"
Technology	SECURITHERM Securitouch sequential thermostatic mixer
Length	184mm
Flow rate	9 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	 
Warranty	