SECURITHERM BIOCLIP thermostatic sink mixer

Ref. H9615

Pillar-mounted thermostatic sequential mixer

2025 UK public price excluding VAT: £662.65



SECURITHERM BIOCLIP thermostatic sink mixer - Ref. H9615

Pillar-mounted thermostatic SECURITHERM sink mixer.

Thermostatic sequential mixer: opens and closes with cold water.

No risk of cross flow between hot and cold water.

No non-return valves on the inlets.

Wall-mounted mixer supplied with 2 stainless steel spouts.

Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails. Securitouch thermal insulation prevents burns.

Scale-resistant thermostatic sequential cartridge for sequential control of flow rate and temperature.

Temperature can be adjusted from cold water up to 40° C with maximum temperature limiter set at 40° C.

Thermal and chemical shocks are possible.

Body and spout with smooth interiors and low water volume.

Flow rate regulated at 7 lpm.

Chrome-plated brass body.

No manual contact thanks to Hygiene control lever L. 146mm.

Thermostatic mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Sequential mixer suitable for people with reduced mobility.

Mixer with 30-year warranty.



ADVANTAGES



Sequential: opens/closes with cold



Maximum hygiene: no non-return



Removable spout: reduces bacterial development



SECURITHERM: optimised antiscalding safety

TECHNICAL CHARACTERISTICS

SECURITHERM BIOCLIP thermostatic sink mixer - Ref. H9615

Connector	M1/2"
Technology	SECURITHERM BIOCLIP sequential mixer
Height	258mm
Spout length	136mm
Flow rate	7 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	•WRAS
Warranty	30 g

