

SECURITHERM shower panel

Ref. 79239015

Thermostatic mechanical dual control

2026 UK public price excluding VAT: £1,133.50

DESCRIPTION

SECURITHERM shower panel - Ref. 79239015

Dual control thermostatic shower panel:
Anodised aluminium shower panel for wall-mounted, exposed installation.
Top inlet via in-line stopcocks and conical Ø 15mm inlets.
SECURITHERM thermostatic mixer.
Adjustable temperature control from cold water to 41°C.
Anti-scalding safety: automatic shut-off if cold or hot water supply fails.
Anti-cold showers function: automatic shut-off if hot water fails.
Thermal shocks are possible.
1/4 turn non-time flow valves.
Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation set at 6 lpm at 3 bar.
Handset with removable flexible via rapid push-fit connector and wall-support supplied.
Concealed fixings.
Filters and non-return valves.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 79239015

Connector	M½" Ø 15mm
Technology	Non-time flow
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	ACS
Warranty	30 YEAR WARRANTY



ADVANTAGES



Thermostatic control



Instant shut-off if cold water supply fails



Fixed shower head or handset



Aluminium body, brass controls

