

SECURITHERM shower panel

Ref. 79239015

Thermostatic mechanical dual control

2026 UK public price excluding VAT: £1,079.52



DESCRIPTION

SECURITHERM shower panel - Ref. 79239015

Dual control thermostatic shower panel:

Anodised aluminium shower panel for wall-mounted, exposed installation.

Top inlet via in-line stopcocks and conical Ø 15mm inlets.

SECURITHERM thermostatic mixer.

Adjustable temperature control from cold water to 41°C.

Anti-scalding safety: automatic shut-off if cold or hot water supply fails.

Anti-cold showers function: automatic shut-off if hot water fails.

Thermal shocks are possible.

1/4 turn non-time flow valves.

Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation set at 6 lpm at 3 bar.

Handset with removable flexible via rapid push-fit connector and wall-support supplied.

Concealed fixings.

Filters and non-return valves.

Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 79239015

Connector	M½" Ø 15mm
Technology	Non-time flow
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	ACS
Warranty	30 <small>YEAR WARRANTY</small>

ADVANTAGES



Thermostatic control



Instant shut-off if cold water supply fails



Fixed shower head or handset



Aluminium body, brass controls

