

Aluminium shower panel with SECURITHERM sequential mixer

Ref. H963915

Sequential thermostatic mixer

2026 UK public price excluding VAT: £861.38

DESCRIPTION

Aluminium shower panel with SECURITHERM sequential mixer - Ref. H963915

SECURITHERM anodised aluminium shower panel for wall-mounted exposed installation:

SECURITHERM sequential thermostatic mixer (non time flow).

Temperature control from cold water up to 39°C.

Maximum temperature limiter set at 39°C, can be adjusted.

Anti-scalding failsafe: automatic shut-off if cold or hot water supply fails.

Thermal shocks are possible.

Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.

Hygiene control lever L. 100mm.

Top inlets with M1/2" stopcocks.

With copper tails.

Concealed fixings and filters.

30-year warranty.

TECHNICAL CHARACTERISTICS

Aluminium shower panel with SECURITHERM sequential mixer - Ref. H963915

Supply	Top inlets via inline stopcocks M1/2"
Connector	M1/2", Ø 15mm
Technology	SECURITHERM single control thermostatic mixer
Height	1050mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	39°C
Finish	Aluminium
Norms	
Warranty	



ADVANTAGES



SECURITHERM: Optimum anti-scalding safety



No non-return valves on inlets



Thermostatic: total temperature stability



Sequential open and closing on cold water

