

SECURITHERM shower panel

Ref. 79240415

Electronic battery-operated thermostatic

2024 UK public price excluding VAT: £1,331.36


DESCRIPTION

SECURITHERM shower panel - Ref. 79240415

Electronic thermostatic shower panel:
Large stainless steel electronic shower panel for wall-mounted, exposed installation.
Top inlet via in-line stopcocks Ø15mm for compression fittings.
SECURITHERM thermostatic shower mixer.
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
Anti-scalding failsafe: automatic shut-off if cold water fails.
Anti-cold showers function: automatic shut-off if hot water fails.
Thermal shocks are possible.
Battery-operated with CR-P2 223 6V Lithium battery.
Infrared presence detection. Shower starts when hand is 4cm from the sensor.
Shuts off on demand or automatically after ~60 seconds.
Duty flush (~60 seconds every 24 hours after the last use).
Flow rate set at 6 lpm at 3 bar.
Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.
With integrated soap dish.
Concealed fixings.
Filters and non-return valves.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 79240415

Supply	6V battery
Connector	M1/2" Ø 15mm
Technology	Electronique
Height	1220mm
Depth	100mm
Width	250mm
Flow rate	6 lpm
Temperature limiter	thermostatic
Finish	Stainless steel
Warranty	



ADVANTAGES



Total hygiene: operate without manual contact



Automatic anti-bacterial proliferation duty flush



Thermostatic temperature regulation



Instant shut-off if cold water fails

