SECURITHERM shower panel

Ref. 792310UK

Thermostatic time flow

2025 UK public price excluding VAT: £916.80



DESCRIPTION

SECURITHERM shower panel - Ref. 792310UK

Thermostatic time flow shower panel:

Anodised aluminium shower panel for wall-mounted, exposed installation. With concealed inlet via flexibles.

SECURITHERM thermostatic shower mixer.

Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.

Anti-scalding safety: automatic shut-off if cold or hot water supply fails.

Anti-cold showers function: automatic shut-off if hot water fails.

Thermal shocks are possible.

Soft-touch operation.

Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head and automatic flow rate regulation.

Time flow shower valve ~30 seconds.

Flow rate 6 lpm at 3 bar.

Concealed fixings.

Filters and non-return valves.

Time flow shower panel suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Thermostatic temperature regulation



Instant shut-off if cold water fails



80% water savings




Aluminium panel, brass controls

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792310UK

Connector	M½"
Technology	Time flow
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Warranty	30 g



© DELABIE https://www.delabie.co.uk