SECURITHERM time flow shower panel

Ref. 79230415

Thermostatic time flow

2025 UK public price excluding VAT: £1,071.59



SECURITHERM time flow shower panel - Ref. 79230415

Thermostatic time flow shower panel:

Large model satin stainless steel shower panel for wall mounted, exposed installation.

Top inlet via in-line stopcocks and Ø 15mm conical inlets.

SECURITHERM thermostatic shower mixer.

Adjustable temperature control from cold water up to 41°C.

Anti-scalding safety: automtaic shut-off if cold or hot water supply fails.

Thermal shocks are possible.

Soft-touch operation.

Time flow ~30 seconds.

Flow rate 6 lpm at 3 bar.

Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.

Integrated soap dish.

Concealed fixings.

Filters and non-return valves.

Suitable for people with reduced mobility

30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM time flow shower panel - Ref. 79230415

Connector	M½'' Ø 15mm
Technology	Time flow
Height	1220mm
Depth	100mm
Width	250mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Stainless steel
Warranty	30 g



ADVANTAGES



Thermostatic temperature regulation




Instant shut-off if cold water fails



80% water savings



Stainless steel panel, brass controls



© DELABIE https://www.delabie.co.uk