

# SECURITHERM shower panel

Ref. 792320

Thermostatic time flow dual control

2024 UK public price excluding VAT: £987.02

## DESCRIPTION

SECURITHERM shower panel - Ref. 792320

SECURITHERM dual control thermostatic time flow shower panel:  
Anodised aluminium shower panel for wall-mounted, exposed installation.  
With top inlet via in-line stopcocks, M $\frac{1}{2}$ ".  
SECURITHERM thermostatic shower mixer.  
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
Anti-scalding failsafe: automatic shut-off if cold water fails.  
Anti-cold showers function: automatic shut-off if hot water fails.  
Thermal shocks are possible.  
Soft-touch operation.  
Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.  
Handset with removable flexible via push-fit rapid STOP connector and wall support supplied.  
2x ~30-second time flow valves to control ROUND shower head and handset on flexible hose.  
Concealed fixings.  
Filters and non-return valves.  
Shower panel suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792320

|                     |   |
|---------------------|---|
| Connector           | M1/2"   |
| Technology          | Time flow   |
| Height              | 1050mm  |
| Depth               | 65mm  |
| Width               | 210mm   |
| Flow rate           | 6 lpm   |
| Temperature limiter | thermostatic  |
| Finish              | Aluminium   |
| Norms               | ACS   |
| Warranty            |    |



## ADVANTAGES



Thermostatic temperature regulation



Immediate shut-off if cold water fails



80% water savings



Aluminium body, brass controls

