

SECURITHERM shower panel

Ref. 792330

Thermostatic time flow dual control

2024 UK public price excluding VAT: £987.02




DESCRIPTION

SECURITHERM shower panel - Ref. 792330

SECURITHERM dual control thermostatic time flow shower panel:
Anodised aluminium shower panel for wall-mounted, exposed installation.
With concealed inlet via flexibles, M1½".
SECURITHERM thermostatic shower mixer.
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
Anti-scalding failsafe: automatic shut-off if cold water fails.
Anti-cold showers function: automatic shut-off if hot water fails.
Thermal shocks are possible.
Soft-touch operation.
Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.
Handset with removable flexible via push-fit rapid STOP connector and wall support supplied.
2x ~30 second time flow valves to control fixed ROUND shower head and handset on flexible hose.
Concealed fixings.
Filters and non-return valves.
Time flow shower panel suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792330

Connector	M1½"
Technology	Time flow
Height	1050mm
Depth	67mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	ACS  
Warranty	



ADVANTAGES



Thermostatic temperature regulation



Immediate shut-off if cold water fails



80% water savings



Aluminium body, brass controls

