

SECURITHERM time flow shower panel

Ref. 792324

Time flow thermostatic and mechanical dual control

2024 UK public price excluding VAT: £1,148.95

DESCRIPTION

SECURITHERM time flow shower panel - Ref. 792324

Thermostatic dual control shower panel:
 Large satin stainless steel shower panel for wall mounted, exposed installation.
 With top inlet via in-line stopcocks, M $\frac{1}{2}$ ".
 SECURITHERM thermostatic shower mixer.
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
 Anti-scalding failsafe: automatic shut-off if cold water fails.
 Anti-cold showers function: automatic shut-off if hot water fails.
 Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.
 Handset with removable flexible via push-fit rapid STOP connector, wall support supplied.
 ~30 second time flow valve with soft-touch operation to control fixed ROUND shower head
 1/4 turn non-time flow valve to control handset with flexible hose.
 Thermal shocks are possible.
 Concealed fixings.
 Filters and non-return valves.
 Shower panel suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM time flow shower panel - Ref. 792324

| | |
|---------------------|---|
| Connector | M $\frac{1}{2}$ " |
| Technology | Non-time flow and time flow |
| Height | 1220mm |
| Depth | 100mm |
| Width | 250mm |
| Flow rate | 6 lpm |
| Temperature limiter | Thermostatic |
| Finish | Stainless steel |
| Norms | ACS   |
| Warranty |  |



ADVANTAGES

-  Thermostatic temperature regulation
-  Immediate shut-off if cold water fails
-  Fixed or handheld shower head
-  Stainless steel body, brass controls

