

# SECURITHERM dual control shower panel

Ref. 792334

Time flow thermostatic and mechanical dual control

2025 UK public price excluding VAT: £1,183.43

## DESCRIPTION

SECURITHERM dual control shower panel - Ref. 792334

Dual control thermostatic shower panel:  
 Large model satin stainless steel shower panel for wall mounted, exposed installation.  
 With concealed inlet via flexibles, M $\frac{1}{2}$ ".  
 SECURITHERM thermostatic shower mixer.  
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
 Anti-scalding failsafe: automatic shut-off if cold water fails.  
 Anti-cold showers function: automatic shut-off if hot water fails.  
 Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.  
 Handset with removable flexible via push-fit rapid STOP connector, wall support supplied.  
 Time flow valve ~30 seconds with soft-touch operation to control the ROUND shower head  
 Non-time flow valve to control the handset with flexible hose.  
 Stopcocks.  
 Concealed fixings.  
 Filters and non-return valves.  
 This product is compatible with thermal and chemical shocks in accordance with current guidelines.  
 Shower panel suitable for people with reduced mobility.  
 30-year warranty.





## TECHNICAL CHARACTERISTICS


SECURITHERM dual control shower panel - Ref. 792334

Connector	M $\frac{1}{2}$ "
Technology	Non-time flow and time flow
Height	1,220mm
Depth	100mm
Width	250mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Stainless steel



## ADVANTAGES

-  Thermostatic temperature regulation
-  Immediate shut-off if cold water fails
-  Fixed or handheld shower head
-  Stainless steel body, brass controls



Norms



---

Warranty

