SECURITHERM dual control shower panel

Ref. 792334

Time flow thermostatic and mechanical dual control

2024 UK public price excluding VAT: £1,148.95



SECURITHERM dual control shower panel - Ref. 792334

Dual control thermostatic shower panel:

Large model satin stainless steel shower panel for wall mounted, exposed installation.

With concealed inlet via flexibles, M½".

SECURITHERM thermostatic shower mixer.

Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.

Anti-scalding failsafe: automatic shut-off if cold water fails.

Anti-cold showers function: automatic shut-off if hot water fails.

Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.

Handset with removable flexible via push-fit rapid STOP connector, wall support supplied.

Time flow valve \sim 30 seconds with soft-touch operation to control the ROUND shower head

Non-time flow valve to control the handset with flexible hose.

Stopcocks.

Concealed fixings.

Filters and non-return valves.

Shower panel suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM dual control shower panel - Ref. 792334

Connector	M½"
Technology	Non-time flow and time flow
Height	1,220mm
Depth	100mm
Width	250mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Stainless steel
Norms	ACS 👪 🔘
Warranty	30 g WARPANTY



ADVANTAGES



Thermostatic temperature regulation



Immediate shut-off if cold water fails



Fixed or handheld shower head



Stainless steel body, brass controls

