

# SECURITHERM shower panel

Ref. 792403CF

Electronic thermostatic battery-operated

2024 UK public price excluding VAT: £1,263.85


## DESCRIPTION

SECURITHERM shower panel - Ref. 792403CF

SECURITHERM electronic thermostatic shower panel:  
Large model stainless steel panel for wall-mounted, exposed installation.  
Top inlet via in-line stopcocks M½".  
SECURITHERM thermostatic shower mixer.  
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
Anti-scalding failsafe: automatic shut-off if cold water fails.  
Anti-cold showers function: automatic shut-off if hot water fails.  
Thermal shocks are possible.  
Battery-operated with CR-P2 223 6V Lithium battery.  
Shower starts when hand is 4cm from the infrared sensor.  
Shuts off on demand or automatically after ~60 seconds.  
Duty flush (~60 seconds every 24 hours after the last use).  
Flow rate 6 lpm at 3 bar.  
Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.  
Concealed fixings.  
Filters and non-return valves.  
Electronic shower panel suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792403CF

|                     |   |
|---------------------|---|
| Supply              | 6V battery  |
| Connector           | M½"   |
| Technology          | Electronic  |
| Height              | 1220mm  |
| Depth               | 100mm   |
| Width               | 250mm   |
| Flow rate           | 10 lpm  |
| Temperature limiter | thermostatic  |
| Finish              | Stainless steel   |
| Norms               | ACS   |
| Warranty            |  |



## ADVANTAGES



Total hygiene: operate without manual contact



Duty flush prevents bacterial proliferation



Thermostatic temperature regulation



Immediate shut-off if cold water fails

