SECURITHERM shower panel

Ref. 792304CF

Time flow thermostatic

2024 UK public price excluding VAT: £1,015.21



DESCRIPTION

SECURITHERM shower panel - Ref. 792304CF

Thermostatic time flow shower panel:

Large model satin stainless steel shower panel for wall mounted, exposed installation.

Top inlet via in-line stopcocks M½".

SECURITHERM thermostatic shower mixer.

Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.

Anti-scalding safety: automatic shut-off if cold or hot water supply fails.

Thermal shocks are possible.

Soft-touch operation.

Time flow ~30 seconds.

Flow rate 6 lpm at 3 bar.

Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.

Integrated soap dish.

Concealed fixings.

Filters and non-return valves.

Shower panel suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792304CF

Connector	M½"
Technology	Time flow
Height	1220mm
Depth	100mm
Width	250mm
Flow rate	10 lpm
Temperature limiter	Thermostatic
Finish	Stainless steel
Norms	ACS
Warranty	30 E WASRANTY

ADVANTAGES



Thermostatic temperature regulation



Immediate shut-off if cold water fails



80% water savings



Stainless steel sheath, brass controls

