

Aluminium shower panel with SECURITHERM sequential mixer

Ref. H9634

Sequential thermostatic

2026 UK public price excluding VAT: £739.32

DESCRIPTION

Aluminium shower panel with SECURITHERM sequential mixer - Ref. [H9634](#)

Anodised aluminium shower panel for wall-mounted exposed installation: SECURITHERM sequential thermostatic mixer (non time flow). Adjustable temperature control from cold water up to 39°C; maximum temperature limiter set at 39°C, can be adjusted. Anti-scalding safety: automatic shut-off if cold water supply fails. Anti-cold showers function: automatic shut-off if hot water fails. Thermal shocks are possible. Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar. Comfort rain-effect spray. Hygiene control lever L. 100mm. Concealed supply via M1/2" flexibles. Concealed fixings. Filters. Suitable for people with reduced mobility. 30-year warranty.

TECHNICAL CHARACTERISTICS

Aluminium shower panel with SECURITHERM sequential mixer - Ref. [H9634](#)

Supply	Concealed, via M1/2" flexible
Connector	M1/2"
Technology	Sequential thermostatic SECURITHERM
Height	1050mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	39°C
Finish	Aluminium
Norms	  
Warranty	



ADVANTAGES



SECURITHERM: Optimum anti-scalding safety




No non-return valves on inlets



Thermostatic: total temperature stability



Sequential open and closing on cold water



Repairability

