

Shower riser rail with EP mechanical mixer

Ref. 2239EPSKIT

Riser rail with pressure-balancing mixer

2026 UK public price excluding VAT: £324.85



DESCRIPTION






Shower riser rail with EP mechanical mixer - Ref. 2239EPSKIT

Shower riser rail with single control mechanical mixer.





- Wall-mounted shower kit.
 - Ø 40mm ceramic cartridge with pressure-balancing (EP) and pre-set maximum temperature limiter.
 - Total anti-scalding safety: HW flow rate is reduced if CW supply fails (and vice versa).
 - Constant temperature regardless of pressure or flow rate variations.
 - Flow rate regulated at 9 lpm.
 - Chrome-plated brass body and sculptured control lever.
 - M½" shower outlet with integrated non-return valve.
 - Mixer with 2 offset standard wall connectors M1/2" M3/4".
 - Filters and non-return valves
 - Chrome-plated sliding shower head (ref. 811) on a chrome-plated riser rail (ref. 820) with soap dish and flexible hose (ref. 834T1).
- Shower riser rail ideal for healthcare facilities, nursing homes, hospitals and clinics.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

Shower riser rail with EP mechanical mixer - Ref. 2239EPSKIT

Connector	M1/2"
Technology	SECURITHERM EP
Width	175mm
Flow rate	9 lpm
Temperature limiter	39°C
Finish	Chrome-plated brass
Norms	  
Warranty	
Repairability	

ADVANTAGES

-  HW flow rate reduced if CW fails
-  Pressure-balancing: constant temperature
-  Ergonomic: sculptured lever is easy to grip
-  Water savings: flow rate regulated at 9 lpm

