

TEMPOFIX 3 frame system for urinals

Ref. 543006D-778700

Time flow flush valve - For urinals with ½" flexible

2021 UK public price excluding VAT: £593.83



DESCRIPTION

TEMPOFIX 3 frame system for urinals - Ref. 543006D-778700

Frame system with time flow urinal valve:
 Black powder-coated steel frame for wall mounted installation. Fixes to floor and load-bearing walls, anchoring bolts supplied.
 Adjustable bracket 95 - 280mm.
 Frame height can be adjusted 0 - 200mm.
 Ø 50mm soil pipe with waterproof seal.
 Delivered pre-mounted.
 Compatible with solid wall finishes from 13 - 120mm.
 10-year warranty.
 Fitted with a TEMPOFLUX F½" time flow flush valve:
 Satin finish stainless steel wall plate 145 x 145mm.
 Chrome-plated metal mush button.
 Waterproof recessing housing.
 Soft-touch operation.
 Time flow pre-set at ~3 seconds.
 Flow rate pre-set at 0.15 L/sec. at 3 bar, can be adjusted to 0.3 L/sec.
 Complies with European standard EN 12541 (class II acoustic level).
 Connection with ½" brass connection (for urinals supplied by flexible).
 Technical features: see TEMPOFLUX urinal ref. 778BOX-778700.
 Kit contents:
 (543006D): frame system, tube with brass union ½" for flexible supply, soil pipe sleeve Ø 50mm, recessed housing with cover, valve configured for system flush, connection accessories.
 (778700): control plate, collar for waterproofing, valve, time flow cartridge, filter and stopcock.

TECHNICAL CHARACTERISTICS

TEMPOFIX 3 frame system for urinals - Ref. 543006D-778700

Connector	½"
Technology	Time flow
Height	985 - 1385mm
Depth	160 - 220mm
Width	430mm
Finish	Satin finish stainless steel
Norms	
Warranty	



ADVANTAGES



Quick and easy to install: delivered pre-mounted



Soft-touch operation



ECO time flow 3 seconds



Install behind wall, on frame system

