## DELABIE

# SECURITHERM EP pressurebalancing shower mixer

Ref. 2539EPS

Wall-mounted single control mixer, sculptured lever

2024 UK public price excluding VAT: £232.66



#### DESCRIPTION

SECURITHERM EP pressure-balancing shower mixer - Ref. 2539EPS

Wall-mounted single control mechanical shower mixer.

Ø 40mm ceramic cartridge with pressure-balancing and pre-set maximum temperature limiter.

Anti-scalding safety: HW flow rate is reduced if CW supply fails (and vice versa).

Stable temperature regardless of pressure and flow rate variations in the system.

Flow rate regulated at 9 lpm.

 $M^{\ensuremath{\sc M^{\ensuremath{\sc M^{\ensuremath{\se M^{\ensuremath}\se M^{\ensuremath{\se M^{\ensuremath}\se M^{\ensuremath{\se M^{\ensuremath{\se M^{\ensuremath{\se M^{\ensuremath}\se M^{\ensuremath}\se M^{\ensuremath{\se M^{\ensuremath}\se M^{\ensuremath}\se M^{\ensurem$ 

Mixer with offset standard wall connectors  $M^{1}\!\!\!/_2"\,M^{3}\!\!\!/_2"$  .

Filters and non-return valves.

Mechanical mixer with SECURITHERM pressure-balancing ideal for healthcare facilities, nursing homes, hospitals and clinics.

Shower mixer suitable or people with reduced mobility.

Mixer with 30-year warranty.

### **TECHNICAL CHARACTERISTICS**

#### SECURITHERM EP pressure-balancing shower mixer - Ref. 2539EPS


Connector	M1/2"
Technology	SECURITHERM EP mechanical mixer
Flow rate	9 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS 🎽 🙆 🖪
Warranty	

#### ADVANTAGES



HW flow rate reduced if CW fails

Pressure-balancing: limits temperature variations



Water savings: flow rate regulated at 9 lpm

