

Auto-draining shower kit with EP mechanical mixer

Ref. 2539EPHYG

Shower kit with pressure-balancing mixer

2025 UK public price excluding VAT: £292.57

DESCRIPTION

Auto-draining shower kit with EP mechanical mixer - Ref. 2539EPHYG

Shower kit with single control mechanical mixer.
SECURITHERM shower kit with auto-draining device:

- Mixer with Ø 40mm ceramic cartridge with pressure-balancing and pre-set maximum temperature limiter.

Anti-scalding safety: HW flow rate is reduced if CW supply fails (and vice versa).
Constant temperature regardless of pressure and flow rate variations.
Flow rate regulated at 9 lpm.
Chrome-plated brass body and sculptured control lever.
M½" shower outlet with integrated non-return valve.
Mixer with 2 offset STOP/CHECK wall connectors M1/2" M3/4" ideal for hospitals.
Filters and non-return valves.

- Chrome-plated shower head (ref. 813) with flexible hose (ref. 834T3) and chrome-plated, wall-mounted tilting support (ref. 845).
- Anti-stagnation connector FM½" for installation between lower outlet and flexible shower hose, for auto-draining of the flexible hose and shower head (ref. 880).

Shower kit ideal for healthcare facilities, nursing homes, hospitals and clinics.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

Auto-draining shower kit with EP mechanical mixer - Ref. 2539EPHYG

Connector	M1/2"
Technology	SECURITHERM EP
Width	175mm
Flow rate	9 lpm
Temperature limiter	39°C
Finish	Chrome-plated brass
Norms	  
Warranty	
Repairability	



ADVANTAGES

-  HW flow rate reduced if CW fails
-  Pressure-balancing: constant temperature
-  Ergonomic: sculptured lever is easy to grip
-  Water saving: flow rate regulated at 9 lpm

