

# BINOPTIC MIX electronic mixer

Ref. 388MCHLH15

Mains supply, Ø 15mm compression fittings

2026 UK public price excluding VAT: £631.99

## DESCRIPTION

**BINOPTIC MIX electronic mixer - Ref. 388MCHLH15**

Deck-mounted electronic basin mixer:  
 Independant IP65 electronic unit.  
 230/12V mains supply with transformer.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
 Scale-resistant flow straightener.  
 Adjustable duty flush (pre-set at 60 seconds every 24 hours after the last use).  
 Optimised active infrared presence detection at the end of the spout.  
 Body in chrome-plated brass.  
 PEX flexibles with filters and Ø 15mm compression fittings.  
 Fixings reinforced by 2 stainless steel rods.  
 Anti-blocking security.  
 Spout with smooth interior and low water volume (reduces niches where bacteria can develop).  
 Side temperature control lever with long lever and adjustable maximum temperature limiter.  
 Drop height: 170mm, for semi-recessed basins.  
 Suitable for people with reduced mobility.  
 30-year warranty.

## TECHNICAL CHARACTERISTICS

**BINOPTIC MIX electronic mixer - Ref. 388MCHLH15**

|               |                                                                                                                                                                         |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supply        | 230/12V mains supply                                                                                                                                                    |
| Connector     | M1/2" Ø 15mm                                                                                                                                                            |
| Technology    | Electronic                                                                                                                                                              |
| Drop height   | 170mm                                                                                                                                                                   |
| Spout length  | 175mm                                                                                                                                                                   |
| Flow rate     | 3 lpm                                                                                                                                                                   |
| Norms         |   |
| Warranty      |                                                                                      |
| Repairability |                                                                                      |



## ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Anti-bacterial duty flush



LED diagnostic aid

