BINOPTIC MIX electronic mixer

Ref. 398MCHLH15

Mains supply, Ø 15mm compression fittings

2025 UK public price excluding VAT: £657.31



BINOPTIC MIX electronic mixer - Ref. 398MCHLH15

Deck-mounted electronic basin mixer:

Independent IP65 electronic control unit.

230/12V mains supply with transformer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush 60 seconds every 24 hours after last use). Active, infrared presence detection, sensor at the end of the spout optimises detection.

Chrome-plated brass body.

PEX flexibles with filters and solenoid valve Ø 15mm compression fittings.

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Spout with smooth interior and low water volume (reduces bacterial development).

Side temperature control with long lever and adjustable maximum temperature limiter.

Drop height: 250mm for countertop washbasins.

Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

BINOPTIC MIX electronic mixer - Ref. 398MCHLH15

Secteur 230/12 V
M1/2" Ø 15
Electronic
250mm
185mm
3 lpm
C E JWRAS
30 E



ADVANTAGES



Exceptional water savings: 90%




Hygiene: no manual contact



Anti-bacterial duty flush



LED diagnostic aid



© DELABIE