

# BINOPTIC electronic tap

Ref. 49801515

Battery-operated, Ø 15mm compression fittings

2026 UK public price excluding VAT: £626.00



## DESCRIPTION

BINOPTIC electronic tap - Ref. 49801515

Deck-mounted electronic basin tap:  
Independent IP65 electronic control unit.  
Battery-operated with 123 6V Lithium batteries.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
Scale-resistant flow straightener.  
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
Active, infrared presence detection, sensor at the end of the spout optimises detection.  
Chrome-plated brass body.  
PEX flexible with filter and solenoid valve Ø 15mm.  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Spout with smooth interior and low water volume (reduces bacterial development).  
Drop height: 250mm for countertop washbasins.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

BINOPTIC electronic tap - Ref. 49801515

|              |              |
|--------------|--------------|
| Supply       | 6V batteries |
| Connector    | M1/2" Ø 15   |
| Technology   | Electronic   |
| Drop height  | 250mm        |
| Spout length | 185mm        |
| Flow rate    | 3 lpm        |
| Norms        |              |
| Warranty     |              |

## ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Duty flush limits bacterial proliferation



LED diagnostic aid

