BINOPTIC electronic tap

Ref. 49801515

Battery-operated, Ø 15mm conical inlets

2024 UK public price excluding VAT: £590.05



DESCRIPTION

BINOPTIC electronic tap - Ref. 49801515

Deck-mounted electronic basin tap:
Independent IP65 electronic control unit.
Battery-operated with 123 6V Lithium batteries.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Active, infrared presence detection, sensor at the end of the spout optimises detection.
Chrome-plated brass body.
PEX flexible with filter and solenoid valve Ø 15mm.
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Spout with smooth interior and low water volume (reduces bacterial development).
Drop height: 250mm for countertop washbasins.
Suitable for people with reduced mobility.
30-year warranty.

ADVANTAGES

- 90% water savings
- Total hygiene: no manual contact
- Anti-bacterial proliferation duty flush
- Sleek design

TECHNICAL CHARACTERISTICS

BINOPTIC electronic tap - Ref. 49801515

Supply	6V batteries
Connector	M1/2'' Ø 15
Technology	Electronic
Drop height	250mm
Spout length	185mm
Flow rate	3 lpm
Norms	WRAS
Warranty	30 YEAR WARRANTY

