

BINOPTIC electronic tap

Ref. 49801515

Battery-operated, Ø 15mm compression fittings

2025 UK public price excluding VAT: £607.77





DESCRIPTION

BINOPTIC electronic tap - Ref. 49801515





Deck-mounted electronic basin tap:
Independent IP65 electronic control unit.
Battery-operated with 123 6V Lithium batteries.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Active, infrared presence detection, sensor at the end of the spout optimises detection.
Chrome-plated brass body.
PEX flexible with filter and solenoid valve Ø 15mm.
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Spout with smooth interior and low water volume (reduces bacterial development).
Drop height: 250mm for countertop washbasins.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

BINOPTIC electronic tap - Ref. 49801515

| | |
|--------------|---|
| Supply | 6V batteries |
| Connector | M1/2" Ø 15 |
| Technology | Electronic |
| Drop height | 250mm |
| Spout length | 185mm |
| Flow rate | 3 lpm |
| Norms |  |
| Warranty |  |

ADVANTAGES

-  Exceptional water savings: 90%
-  Hygiene: no manual contact
-  Duty flush limits bacterial proliferation
-  LED diagnostic aid

