

Sequential mechanical basin mixer

Ref. 2641S

Sequential mechanical mixer with fixed spout L. 200mm

2024 UK public price excluding VAT: £344.41



DESCRIPTION

Sequential mechanical basin mixer - Ref. 2641S

Wall-mounted sequential mechanical basin mixer.
Mechanical sequential mixer: opens and closes on cold water, with 70° turning range.

Wall-mounted mixer with swivelling under spout L. 200mm with hygienic BIOSAFE outlet.

Spout suitable for fitting a BIOFIL point-of-use filter.

Spout can be easily fixed in place.

Securitouch thermal insulation prevents burns.

Ø 35mm classic ceramic cartridge with pre-set maximum temperature limiter.
Body and spout with narrow tubes with smooth interiors and very low water volume.

The speed of the water reduces the development of biofilm.

Thermal shocks are possible without removing the control lever or shutting off the cold water supply.

Flow rate regulated at 5 lpm.

Chrome-plated brass body.

Hygiene control lever L. 150mm requires no manual contact.

Mixer supplied with offset standard wall connectors M1/2" M3/4".

Recommended installation height: 110 - 200mm above the basin surface.

Mechanical mixer ideal for Healthcare facilities, retirement and care homes, hospitals and clinics.

Sequential mixer suitable for people with reduced mobility.

Mixer with 30-year warranty.

ADVANTAGES



Sequential: opens/closes with cold water



Thermal shocks are possible without removing lever





Maximum hygiene: prevents biofilm



Spout can be fixed or swivel

TECHNICAL CHARACTERISTICS

Sequential mechanical basin mixer - Ref. 2641S

Connector	M1/2"
Technology	BIOSAFE sequential mechanical mixer
Spout length	200mm
Flow rate	5 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS  
Warranty	