DELABIE

TEMPOFIX 3 frame system for urinals

Ref. 543100

Electronic urinal valve with mains supply

2024 UK public price excluding VAT: £836.82

DESCRIPTION

TEMPOFIX 3 frame system for urinals - Ref. 543100

Frame system with electronic urinal valve: Black powder-coated steel frame for wall-mounted installation. Fixes to floor and load-bearing walls, anchoring bolts supplied. Adjustable bracket 95 - 280mm. Frame height can be can be adjusted 0 - 200mm. Ø 50mm soil pipe with waterproof seal. Delivered pre-mounted. Compatible with solid wall finishes from 40 - 190mm.

Fitted with a TEMPOMATIC M¹/₂" electronic urinal valve: Mains supply, 12V electronic control unit with solenoid valve, filter and stopcock. Shock-resistant infrared presence detection sensor. Detection distance, time flow and flow rate can be adjusted during installation. Install a 230/12V transformer. Detection delay is 3 seconds. Automatic pre-rinse is possible. Time flow pre-set at 3 seconds, can be adjusted from 3 - 12 seconds. Hygienic duty flush every 24 hours after the last use: prevents vacuums. Flow rate 0.3 L/sec. at 3 bar, can be adjusted. Wall plate is flush to the wall. Threaded rods can be cut to size. Compatible with rain water. Suitable for people with reduced mobility. Technical features: see TEMPOMATIC urinal valve ref. 428200. 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOFIX 3 frame system for urinals - Ref. 543100

Supply	Mains supply 230/12V
Connector	1⁄2"
Technology	Electronic
Height	985 - 1385mm
Depth	160 - 220mm
Width	430mm
Warranty	30 MARANTY



Hygienic duty flush

