

SPORTING 2 SECURITHERM

electronic shower panel

Ref. 714910

Mains, thermostatic, scale-resistant nozzle

2024 UK public price excluding VAT: £438.04

DESCRIPTION

SPORTING 2 SECURITHERM electronic shower panel - Ref. 714910

SPORTING 2 SECURITHERM, thermostatic electronic shower panel:
Recessed inlets.
Anodised aluminium and chrome-plated satin finish panel.
Mains supply 230/6V.
Infrared presence detection. Shower starts when hand is moved towards the sensor (detection distance ~4cm).
Shuts off voluntarily or automatically after ~60 seconds.
Duty flush (~60 seconds every 24 hours after the last use).
Flow rate 6 lpm at 3 bar.
Tamperproof, scale-resistant fixed shower head with automatic flow rate regulation.
Accessible filters and non-return valves.
Integrated stopcocks.
M1½" recessed connections.
Electronic shower panel suitable for people with reduced mobility.
30-year warranty.
SECURITHERM technology:
Thermostatic shower mixer directly integrated in the head of the shower panel.
Temperature set by the installer.
Stable temperature, pre-set at 38°C.
Anti-scalding failsafe: automatic shut-off if the cold water fails.
Anti-cold showers function: automatic shut-off if the hot water fails.
Order with support bracket reference 714012.

TECHNICAL CHARACTERISTICS

SPORTING 2 SECURITHERM electronic shower panel - Ref. 714910

Supply	Mains supply 230/6V
Connector	M1½"
Technology	Electronic
Height	1020mm
Depth	21mm
Width	70mm
Flow rate	6 lpm
Finish	Aluminium
Norms	ACS WRAS



ADVANTAGES



80% water savings




Anti-bacterial proliferation duty flush



Immediate shut-off if cold water fails



Sleek shapes, concealed fixings



Warranty

