SPORTING 2 SECURITHERM electronic shower panel

Ref. 714910

Mains, thermostatic, rain-effect spray, kit 2/2

2025 UK public price excluding VAT: £458.94



SPORTING 2 SECURITHERM electronic shower panel - Ref. 714910

SPORTING 2 SECURITHERM, thermostatic electronic shower panel: Recessed inlets.

Anodised aluminium and chrome-plated satin finish panel.

Mains supply 230/6V.

Infrared presence detection. Shower starts when hand is moved towards the sensor (detection distance ~4cm).

Shuts off voluntarily or automatically after ~60 seconds.

Duty flush (~60 seconds every 24 hours after the last use).

Flow rate 6 lpm at 3 bar, comfortable rain-effect spray.

Tamperproof, fixed shower head with automatic flow rate regulation.

Accessible filters and non-return valves.

Integrated stopcocks.

M½" connections (compact nanny joint, kit 1/2).

Electronic shower panel suitable for people with reduced mobility.

30-year warranty.

SECURITHERM technology:

Thermostatic shower mixer directly integrated in the head of the shower panel.

Temperature set by the installer.

Stable temperature, pre-set at 38°C.

Anti-scalding failsafe: automatic shut-off if the cold water fails.

Prevents cold showers: automatic shut-off if the hot water fails.

Order with nanny joint reference 714012.

TECHNICAL CHARACTERISTICS

SPORTING 2 SECURITHERM electronic shower panel - Ref. 714910

| Supply | Mains supply 230/6V |
|------------|---------------------|
| Connector | M½" |
| Technology | Electronic |
| Height | 1020mm |
| Depth | 21mm |
| Width | 70mm |
| Flow rate | 6 lpm |
| Finish | Aluminium |
| | |



ADVANTAGES



Exceptional water savings: 80%




Anti-bacterial proliferation duty



Immediate shut-off if cold water



Sleek shapes, concealed fixings



DELABIE

| Norms | ACS | WRAS APPECYTO PRISECT | BELGAQUA | $oldsymbol{B}$ |
|----------|-------|--------------------------|----------|----------------|
| | C€ | | | |
| Warranty | 30 gg | | | |

© DELABIE https://www.delabie.co.uk