

SPORTING 2 SECURITHERM

electronic shower panel

Ref. 714900DP

Mains, thermostatic, rain effect

2024 UK public price excluding VAT: £538.03



DESCRIPTION

SPORTING 2 SECURITHERM electronic shower panel - Ref. 714900DP

Thermostatic electronic shower panel - top inlets:
Anodised aluminium and chrome-plated satin finish panel.
Extra flat structure with concealed fixings.
Mains supply 230/6V.
Infrared presence detection. Shower starts when hand is moved towards the sensor (detection distance ~4cm).
Shuts off voluntarily or automatically after ~60 seconds.
Duty flush (~60 seconds every 24 hours after the last use).
Flow rate 6 lpm at 3 bar.
Fixed shower head with rain-effect.
Accessible filters and non-return valves.
Integrated stopcocks.
M½" connection for top inlet.
Electronic panel suitable for people with reduced mobility.
30-year warranty.
SECURITHERM technology:
Thermostatic shower mixer directly integrated in the head of the shower panel.
Temperature set by the installer.
Stable temperature, pre-set at 38°C.
Anti-scalding failsafe: automatic shut-off if the cold water fails.
Anti-cold showers function: automatic shut-off if the hot water fails.

TECHNICAL CHARACTERISTICS

SPORTING 2 SECURITHERM electronic shower panel - Ref. 714900DP

Supply	Mains supply 230/6V
Connector	M½"
Technology	Electronic
Height	1020mm
Depth	21mm
Width	70mm
Flow rate	6 lpm
Finish	Aluminium
Norms	ACS   
Warranty	



ADVANTAGES



80% water savings



Anti-bacterial proliferation duty flush



Immediate shut-off if cold water fails



Sleek shapes, concealed fixings

