

# TEMPOMATIC 4 electronic tap

Ref. 443436

Integrated batteries

2025 UK public price excluding VAT: £363.97



## DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref. 443436

Wall-mounted electronic basin tap:  
 Battery-operated with integrated 123 6V Lithium batteries.  
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the tap.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
 Scale-resistant flow straightener.  
 Duty flush (~60 seconds every 24 hours after last use).  
 Presence detection sensor at the end of the spout optimises detection.  
 Chrome-plated stainless steel body L. 130mm.  
 Cap fixed in place by 2 concealed screws.  
 Anti-blocking security.  
 Stopcock.  
 Wall-mounted.  
 Suitable for people with reduced mobility.  
 30-year warranty.

## ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Batteries integrated into the body of the tap



Replace batteries without removing tap

## TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref. 443436

|               |                                                                                                                                                                                                                                                             |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supply        | 6V batteries                                                                                                                                                                                                                                                |
| Connector     | M1/2"                                                                                                                                                                                                                                                       |
| Technology    | Electronic                                                                                                                                                                                                                                                  |
| Spout length  | 130mm                                                                                                                                                                                                                                                       |
| Flow rate     | 3 lpm                                                                                                                                                                                                                                                       |
| Norms         |    |
| Warranty      |                                                                                                                                                                          |
| Repairability |                                                                                                                                                                          |

