Recessed waterproof housing for BINOPTIC

Ref. 370SBOX

Mains supply, kit 1/2

2025 UK public price excluding VAT: £186.64



ADVANTAGES



Installation recessed in wall



230/6V mains supply



100% waterproof housing

DESCRIPTION

Recessed waterproof housing for BINOPTIC - Ref. 370SBOX

Recessed waterproof housing for BINOPTIC 2, kit 1/2: Mains supply 230/6V (cable and transformer supplied). Recessed waterproof housing:

- Collar with waterproof seal.
- Hydraulic connection from the exterior and maintenance from the front.
- Modular installation (rails, solid walls, panels).
- Compatible with walls from 10 to 120mm (whilst maintaining the minimum recessing depth of 83mm).
- Adaptable standard pipework or "pipe in pipe".
- Integrated stopcock and flow rate adjuster, filter and solenoid valve are accessible from the front.
- BINOPTIC 2 tap F½".
- Supplied in 2 kits: secured system purge without sensitive elements. 30-year warranty.

Order with control plate references: 370100 or 370110.

TECHNICAL CHARACTERISTICS

Recessed waterproof housing for BINOPTIC - Ref. 370SBOX

Connector	F½"
Height	150mm
Depth	83-190mm
Width	175mm
Norms	ACS
Warranty	30 g



