DELABIE

SECURITHERM EP BIOSAFE pressure-balancing basin mixer

Ref. 2921LEP

Single hole mechanical mixer H. 100mm L. 110mm

2025 UK public price excluding VAT: £287.11

DESCRIPTION

SECURITHERM EP BIOSAFE pressure-balancing basin mixer - Ref. 2921LEP

Deck-mounted mechanical basin mixer with pressure-balancing. Single hole mixer with spout H. 100mm L. 110mm fitted with a BIOSAFE hygienic outlet.

Spout suitable for fitting a BIOFIL point-of-use filter.

 \varnothing 35mm ceramic cartridge with pressure-balancing and pre-set maximum temperature limiter.

Anti-scalding safety: HW flow rate is reduced if CW supply fails (and vice versa).

Stable temperature regardless of pressure and flow rate variations in the system.

Spout with a tube with a smooth interior, no niches where bacteria can develop, and low water volume.

The speed with which the water flows through the tube considerably reduces biofilm development.

Thermal shocks are possible without removing the lever or shutting off the cold water supply.

Body with very flow water volume (reduces bacterial development).

Flow rate regulated at 5 lpm.

Hygiene control lever L. 150mm.

No pop-up waste.

F3/8" rotating PEX flexibles with filters and non-return valves.

Fixing reinforced via 2 stainless steel rods.

Mechanical mixer with SECURITHERM pressure-balancing ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Single hole mixer suitable for people with reduced mobility.

Mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM EP BIOSAFE pressure-balancing basin mixer - Ref.

2921LEP

Connector	F3/8"
Technology	SECURITHERM EP BIOSAFE mechanical mixer
Drop height	100mm
Spout length	110mm
Flow rate	5 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass



ADVANTAGES



HW flow rate reduced if CW supply fails




Hygiene: body with very low water volume



Thermal shock without removing the control lever



Pre-set maximum temperature limiter



DELABIE

Norms		WRAS
Warranty	30 MARANTY	
Repairability	50 REPAIRABILITY	