

SECURITHERM time flow shower kit

Ref. 792219

Thermostatic time flow, kit 2/2

2025 UK public price excluding VAT: £652.91





DESCRIPTION

SECURITHERM time flow shower kit - Ref. 792219

Recessed thermostatic time flow shower, kit 2/2:
 Tamperproof polished satin stainless steel plate 195 x 220mm.
 SECURITHERM thermostatic mixer ¾".
 Anti-scalding failsafe: automatic shut-off if cold water fails.
 Anti-cold showers function: automatic shut-off if hot water fails.
 Adjustable temperature from 32° to 40°C, pre-set at 38°C.
 Soft-touch operation.
 Time flow ~30 seconds.
 Flow rate set at 6 lpm at 3 bar.
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
 Concealed fixings, M½" stopcocks.
 Integrated non-return valves and filters.
 Chrome-plated Bayblend® control knob.
 Suitable for people with reduced mobility.
 30-year warranty.
 Order with waterproof housing ref. 792BOX.

TECHNICAL CHARACTERISTICS

SECURITHERM time flow shower kit - Ref. 792219

| | |
|------------|---|
| Connector | ½" |
| Technology | Time flow |
| Height | 195mm |
| Depth | 110mm |
| Width | 220mm |
| Flow rate | 6 lpm |
| Finish | Satin finish stainless steel |
| Norms |    |
| Warranty |  |



ADVANTAGES



Thermostatic temperature control



Instant shut-off if cold water fails



80% water savings

