SECURITHERM time flow shower mixer

Ref. 792218

Thermostatic time flow, kit 2/2

2025 UK public price excluding VAT: £560.54



SECURITHERM time flow shower mixer - Ref. 792218

Recessed thermostatic time flow shower mixer:

Tamperproof satin finish stainless steel control plate 195 x 220mm.

Anti-scalding failsafe: automatic shut-off if cold water fails.

Anti-cold showers function: automatic shut-off if hot water fails.

Temperature can be adjusted from 32 to 40°C, pre-set at 38°C.

Soft-touch operation.

Time flow ~30 seconds.

Flow rate set at 9 lpm at 3 bar.

Concealed fixings, stopcocks M½".

Integrated non-return valves and filters.

Chrome-plated Bayblend® control knob.

Suitable for people with reduced mobility.

30-year warranty.

Order with recessed housing ref. 792BOX.

TECHNICAL CHARACTERISTICS

SECURITHERM time flow shower mixer - Ref. 792218

Technology Time flow Height 195mm Depth 110mm Width 220mm Flow rate 9 lpm Finish Satin finish stainless steel Norms ACS TIME flow Norms Time flow 195mm ACS TIME flow TIME flo	Connector	1/2"
Depth 110mm Width 220mm Flow rate 9 lpm Finish Satin finish stainless steel Norms ACS 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Technology	Time flow
Width 220mm Flow rate 9 lpm Finish Satin finish stainless steel Norms ACS THE LOAD ACS THE	Height	195mm
Flow rate 9 lpm Finish Satin finish stainless steel Norms ACS FIEDARUA DE CONTROLLES STEEL	Depth	110mm
Norms Satin finish stainless steel Norms ACS FINANDA	Width	220mm
Norms ACS BEIGAGUA	Flow rate	9 lpm
BELGAQUA PROPERTY ANTITION	Finish	Satin finish stainless steel
Warranty 30 to wassanty	Norms	PZN
	Warranty	30 g



ADVANTAGES



Thermostatic temperature control




Instant shut-off if cold water supply fails




80% water savings



System tested to over 500,000 operations





© DELABIE