

# TEMPOFIX 3 self-supporting frame system for WCs

Ref. 564005DE

For dual control TEMPOMATIC electronic mains supply valve - Ø 110mm

**2025 UK public price excluding VAT: £435.99**

## DESCRIPTION

**TEMPOFIX 3 self-supporting frame system for WCs - Ref. 564005DE**

Self-supporting frame system for wall-hung WCs, kit 1/2:

Black powder-coated steel frame:

- With large feet for fixing to load-bearing floors.
- Frame height can be adjusted from 0 - 200mm (with 1m mark).
- Compatible with solid walls from 10 - 120mm.
- Ø 32mm flush tube with Ø 55mm connection washer.
- ABS soil pipe, Ø 110mm HDPE outlet with waterproof seal, with 2 setting positions.

Recessed waterproof housing: flush system without cistern, directly connected to pipework.

- Compatible with TEMPOMATIC dual control or TEMPOMATIC Connect electronic WC valves.

- Compatible with 230/6V mains supply.

- Backflow prevention device inside the housing.

- Integrated stopcock and flow rate regulation.

Supplied pre-mounted.

30-year warranty.

Order with control plate references 464000, 464050, 465000 or 465050.

## TECHNICAL CHARACTERISTICS

**TEMPOFIX 3 self-supporting frame system for WCs - Ref. 564005DE**

|            |                                                                                     |
|------------|-------------------------------------------------------------------------------------|
| Connector  | 3/4"                                                                                |
| Technology | Electronic and time flow                                                            |
| Height     | 1000 to 1320mm                                                                      |
| Depth      | 157 - 177mm                                                                         |
| Width      | 350mm                                                                               |
| Diameter   | Ø 110mm outlet                                                                      |
| Finish     | Black powder-coated steel                                                           |
| Warranty   |  |



## ADVANTAGES



Quick and easy to install: delivered pre-mounted



Space-saving



Adapt to wall thickness



Compatible with mains supply

