DELABIE

TEMPOFIX 3 wall-mounted frame system for WCs

Ref. 564060DE

For time flow or battery-operated electronic valve - Ø 110mm outlet

2024 UK public price excluding VAT: £444.61

DESCRIPTION

TEMPOFIX 3 wall-mounted frame system for WCs - Ref. 564060DE

Wall-mounted frame system for wall-hung WCs, kit 1/2: Black powder-coated steel frame:

- For fixing to load-bearing walls.
- Frame height can be adjusted from 0 200mm (with 1m mark).
- Compatible with solid walls from 10 120mm.
- Ø 32mm flush tube with Ø 55mm connection washer.
- ABS soil pipe, Ø 110mm HDPE outlet with waterproof seal, with 2 setting positions.

Recessed waterproof housing: flush system without cistern, directly connected to pipework.

- Compatible with electronic or time flow valves for WCs.
- Compatible with CR123 Lithium 6V battery.
- Backflow prevention device inside the housing.
- Integrated stopcock and flow rate regulation.
- Supplied pre-mounted.
- 30-year warranty.

Order with control plate references 464006, 465006, 763000, 763030, 763040 or 763041.

TECHNICAL CHARACTERISTICS

TEMPOFIX 3 wall-mounted frame system for WCs - Ref. 564060DE

Connector	3/4"
Technology	Electronic and time flow
Height	1000 to 1320mm
Depth	157 - 177mm
Width	350mm
Diameter	Ø 110mm outlet
Finish	Black powder-coated steel
Warranty	



ADVANTAGES



Quick and easy to install: delivered pre-mounted

Space-saving



Adapt to wall thickness



Compatible with 6V Lithium batteries



