

# BIOFIL 2-month filter for taps and exposed showers

Ref. 20250

Sterile

2024 UK public price excluding VAT: £84.90



## DESCRIPTION

**BIOFIL 2-month filter for taps and exposed showers - Ref. 20250**

BIOFIL anti-legionella and all-germ filter for taps and exposed showers, shower spray.

Device material: ABS.

Type of membrane: tubular microfiltration.

Membrane material: Polyethylene.

Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.

Qualified water volume per duration of use: 6,000 litres.

Filtration flow rate: 3 lpm at 1 bar, 5.5 lpm at 3 bar and 7.4 lpm at 5 bar (filter only, excludes any flow rate restriction in the tap).

Space saving, suitable for taps with a low spout height: H. 44mm, Ø 46mm.

Controlled management of retro-contamination: protective skirt and angled connector for optimal positioning (filter position can be adjusted so the water does not flow directly on to the waste).

Maximum upstream pressure at the point-of-use: 5 bar.

Maximum lifespan: 2 months after installation.

Withstands thermal shocks: 70°C for 30 minutes.

Withstands chemical shocks: active chlorine levels up to 100 ppm for 2 hours (cumulative total).

Sterile filter. Individually wrapped.

CE Class Is medical device.

Single unit. Can only be ordered in multiples of 10. Packaged in boxes of 10.

## TECHNICAL CHARACTERISTICS

**BIOFIL 2-month filter for taps and exposed showers - Ref. 20250**

| Technology | Point-of-use filtration                               |
|------------|---|
| Height     | 44mm  |
| Flow rate  | 3 lpm at 1 bar, 5.5 lpm at 3 bar and 7.4 lpm at 5 bar |
| Diameter   | 56mm  |
| Lifespan   | 2 months  |
| Norms      | ACS WWRAS KTW BWGL CE                                 |

## ADVANTAGES



Anti-Legionella and all-germ



Space saving



Optimised positioning: tilting connector



Lifespan: 2 months after installation

