

BIOFIL 2-month tap and wall shower filter

Ref. 30250

Non-sterile

2026 UK public price excluding VAT: £80.98



DESCRIPTION

BIOFIL 2-month tap and wall shower filter - Ref. 30250

BIOFIL anti-Legionella and all-germ tap and wall shower filter, shower spray. Device made from ABS. Membrane type: tubular microfiltration. Membrane made from polyethylene. Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade. Qualified water volume per duration of use: 6,000 litres. Filtration flow rate: 3 lpm at 1 bar, 5.5 lpm at 3 bar and 7.4 lpm at 5 bar (filter only, excludes any flow rate restriction in the tap). Space saving, suitable for taps with a low spout height: H. 44mm, Ø 46mm. Controlled management of retro-contamination: protective skirt and angled connector for optimal positioning (filter position can be adjusted so the water does not flow directly on to the waste). Maximum upstream pressure at the point-of-use: 5 bar. Maximum lifespan: 2 months after installation. Resistance to thermal shocks: 70°C for 30 minutes. Resistance to chemical shocks: active chlorine levels up to 100 ppm for 2 hours (cumulative total). Non-sterile filter. Medical device CE Class I. Packaged individually. Must be ordered in quantities of 10. Packaged in boxes of 10 units.





TECHNICAL CHARACTERISTICS

BIOFIL 2-month tap and wall shower filter - Ref. 30250

Technology	Point-of-use filtration
Height	44mm
Flow rate	3 lpm at 1 bar, 5.5 lpm at 3 bar and 7.4 lpm at 5 bar
Diameter	56mm
Lifespan	2 months

Norms	ACS	WRAS	KTW BWGL	CE

ADVANTAGES

-  Anti-Legionella and all-germ
-  Space saving
-  Optimised position: angled connection
-  Lifespan: 2 months after installation

