

BIOFIL 2-month tap and wall shower filter

Ref. 30251

Non-sterile

2024 UK public price excluding VAT: £76.33



DESCRIPTION

BIOFIL 2-month tap and wall shower filter - Ref. 30251

BIOFIL anti-Legionella and all-germ tap and wall-mounted shower filter, laminar flow.
Device made from ABS.
Membrane type: tubular microfiltration.
Membrane made from polyethylene.
Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.
Qualified water volume per duration of use: 6,000 litres.
Filtration flow rate: 3 lpm at 1 bar, 5.5 lpm at 3 bar and 7.4 lpm at 5 bar (filter only, excludes any flow rate restriction in the tap).
Space saving, suitable for taps with a low spout height: H. 44mm, Ø 46mm.
Controlled management of retro-contamination: protective skirt and angled connector for optimal positioning (filter position can be adjusted so the water does not flow directly on to the waste).
Maximum upstream pressure at the point-of-use: 5 bar.
Maximum lifespan: 2 months after installation.
Resistance to thermal shocks: 70°C for 30 minutes.
Resistance to chemical shocks: active chlorine levels up to 100 ppm for 2 hours (cumulative total).
Non-sterile filter.
CE Class I medical device.
Packaged individually. Must be ordered in quantities of 10. Packaged in boxes of 10 units.

ADVANTAGES



Anti-Legionella and all-germ



Space saving




Optimised position: angled connection



Lifespan: 2 months after installation

TECHNICAL CHARACTERISTICS

BIOFIL 2-month tap and wall shower filter - Ref. 30251

Technology	Point-of-use filtration
Height	44mm
Flow rate	3 lpm at 1 bar, 5.5 lpm at 3 bar and 7.4 lpm at 5 bar
Diameter	56mm
Lifespan	2 months
Norms	ACS  KTW 