DELABIE

Shower riser rail with SECURITHERM thermostatic mixer

Ref. H9768KIT

Shower kit with H9768 thermostatic mixer

2024 UK public price excluding VAT: £506.26

DESCRIPTION

Shower riser rail with SECURITHERM thermostatic mixer - Ref. H9768KIT

Shower riser rail with thermostatic dual control mixer.

Shower kit with SECURITHERM thermostatic shower mixer.

Thermostatic mixer with no non-return valves on the inlets (reduces bacterial proliferation).

No risk of cross flow between hot and cold water.

Mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.

Prevents cold showers: shuts off automatically if hot water supply fails. Securitouch thermal insulation prevents burns.

Scale-resistant thermostatic cartridge adjusts the temperature.

1/4-turn ceramic valve head adjusts the flow rate.

Temperature control up to 43°C.

Double temperature limiter: 1st limiter set at 41°C, 2nd limiter set at 43°C. Thermal shocks are possible without removing the control knob or shutting off the cold water.

Flow rate limited to 9 lpm at 3 bar.

Body made from chrome-plated brass, and with ERGO control knobs.

M1/2" bottom outlet.

Filters integrated in the inlets, F3/4".

Mixer with offset STOP/CHECK wall connectors, M1/2" M3/4".

• Sliding shower head holder (ref. 813) on a chrome-plated riser rail (ref. 821)

with soap dish and flexible shower hose (ref. 836T1).

• Shower head retaining collar (ref. 830).

Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Mixer suitable for people with reduced mobility.

Shower kit with 30-year warranty.

TECHNICAL CHARACTERISTICS

Shower riser rail with SECURITHERM thermostatic mixer - Ref. H9768KIT

Technology	SECURITHERM thermostatic shower mixer with no non-return valves
Depth	87mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS
Warranty	30 B



ADVANTAGES



Total hygiene: mixer with no nonreturn valves



scalding safety

SECURITHERM: optimised anti-



Thermostatic: total temperature stability



Securitouch thermal insulation prevents burns

