DELABIE

SECURITHERM BIOCLIP sequential thermostatic sink mixer

Ref. H9625610

Removable sequential thermostatic mixer H. 160mm L. 140mm

2025 UK public price excluding VAT: £550.73

DESCRIPTION

SECURITHERM BIOCLIP sequential thermostatic sink mixer - Ref. H9625610

Deck-mounted thermostatic SECURITHERM sink mixer. Sequential thermostatic mixer: opens and closes with cold water. No risk of cross flow between the hot and cold water. No non-return valves on the inlets. BIOCLIP: mixer is easy to remove for cleaning and disinfection.

Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails. Securitouch thermal insulation prevents burns.

Single hole mixer with curved spout H. 160mm L. 140mm fitted with a hygienic flow straightener with no impurity retention and thermal shock-resistant. Scale-resistant sequential thermostatic cartridge for single control of flow rate and temperature.

Temperature adjusts from cold water up to 40° C with temperature limiter set at 40° C.

Thermal and chemical shocks are possible.

Body and spout with smooth interiors and low water volume.

Flow rate 9 lpm at 3 bar.

No manual contact thanks to Hygiene control lever L. 146mm. No pop-up waste.

Supplied with copper tails with chrome-plated stopcocks.

Fixing reinforced by 2 stainless steel rods.

Thermostatic mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Sequential mixer suitable for people with reduced mobility.

30-year warranty.

Also available with PEX flexibles.

TECHNICAL CHARACTERISTICS

SECURITHERM BIOCLIP sequential thermostatic sink mixer - Ref. H9625610

Supply	3/8", Ø 15mm
Technology	Removable sequential thermostatic mixer
Drop height	160mm
Spout length	140mm
Flow rate	9 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass





Maximum hygiene: mixer with no non-return valves




Hygiene: can be removed for internal cleaning



SECURITHERM: optimal anti-scalding safety



Sequential: opens and closes with cold water



DELABIE

Warranty	30 KA
Repairability	REZARABILITY