

BIOSAFE sequential mechanical sink mixer

Ref. 2665T3

Tall, single hole sequential mixer H. 300mm L. 160mm

2026 UK public price excluding VAT: £325.66



DESCRIPTION

BIOSAFE sequential mechanical sink mixer - Ref. 2665T3

Deck-mounted tall mechanical sink mixer.

Sequential mechanical mixer: opens and closes with cold water over a range of 70°.

Single hole mixer with fixed spout H. 300mm L. 160mm.

Tall mixer with BIOSAFE hygienic outlet suitable for fitting a BIOFIL terminal filter.

Ø 35 sequential ceramic cartridge with pre-set maximum temperature limiter.

Spout with internal tube with smooth interior and very low water volume.

The speed of the water inside this tube reduces biofilm development considerably.

Thermal shocks are possible without removing the control lever or shutting off the cold water supply.

Body with very volume of water (no niches where bacteria can develop).

Flow rate regulated at 5 lpm.

Hygiene control lever L. 200mm requires no manual contact.

F3/8" rotating PEX flexibles.

No risk of cross flow between the hot and cold water.

No non-return valves on the inlets.

Fixings reinforced by 2 stainless steel rods.

Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.


Mixer suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

BIOSAFE sequential mechanical sink mixer - Ref. 2665T3

Connector	3/8"
Technology	Sequential mechanical mixer
Drop height	300mm
Spout length	160mm
Flow rate	5 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	 
Warranty	



Repairability

