

# Recessed housing for thermostatic shower mixers

Ref. H96BOX

Sequential mixer, kit 1/2

2026 UK public price excluding VAT: £314.87



## DESCRIPTION

Recessed housing for thermostatic shower mixers - Ref. H96BOX

Recessed waterproof housing for thermostatic sequential shower mixers, kit 1/2:

- Collar with waterproof seal.
- Hydraulic connection to the outside and maintenance from the front.
- Water supply connects to the top.
- Adjusts to all types of installation (rails, solid walls, panels).
- Compatible with wall finishes from 10 - 120mm (while maintaining the minimum recessing depth of 83mm).
- Suitable for standard or "pipe-in-pipe" supply.
- Stopcocks and flow rate adjustment, filters and cartridge are all integrated and accessible from the front.
- Thermostatic sequential shower mixer.
- Supplied in 2 kits: secure system flush without sensitive elements.

30-year warranty.  
Order with control-plate reference H9631.

## TECHNICAL CHARACTERISTICS

Recessed housing for thermostatic shower mixers - Ref. H96BOX

|            |  |
|------------|--|
| Connector  | 1/2"   |
| Technology | SECURITHERM Securitouch thermostatic sequential mixer  |
| Depth      | 80 - 110mm   |
| Width      | 225mm  |
| Norms      | <b>ACS</b>  |
| Warranty   | <b>30</b> <small>YEAR</small><br><small>WARRANTY</small>                                       |

## ADVANTAGES

-  Recessed installation
-  Modular and adjustable waterproof housing
-  Sequential mixer: no non-return valves
-  100% waterproof housing

