Recessing housing for thermostatic shower mixers

Ref. H96CBOX

Sequential mixer, kit 1/2

2026 UK public price excluding VAT: £369.03



DESCRIPTION

Recessing housing for thermostatic shower mixers - Ref. H96CBOX

Waterproof recessing housing for sequential thermostatic shower mixer, kit 1/2:
- Collar with waterproof seal.
- Hydraulic connection from the outside and maintenance from the front.
- Water supply connects from the top.
- Adjusts to all types of installations (rails, solid walls, panels).
- Compatible with wall finishes 10 - 110mm (while maintaining the minimum recessing depth of 83mm).
- Suitable for standard or "pipe-in-pipe" supply.
- Stopcocks and flow rate adjustment, filters and cartridge are all integrated and accessible from the front.
- Sequential thermostatic shower mixer.
- Supplied in 2 kits: secure system flush without sensitive elements.
30-year warranty.
Order with the control plate reference H9633.

ADVANTAGES

- Recessed installation
- Modular and adjustable waterproof housing
- Sequential mixer: no non-return valves
- 100% waterproof housing

TECHNICAL CHARACTERISTICS

Recessing housing for thermostatic shower mixers - Ref. H96CBOX

Connector	1/2"
Technology	SECURITHERM Securitouch sequential thermostatic mixer
Depth	83-110mm
Width	225mm
Norms	ACS WRAS
Warranty	30 YEAR WARRANTY



